

# Target Fire Hose

- BS 6391 Type 3 construction
- Maintenance free
- Excellent weathering resistance
- Lightweight
- Good heat resistance



## Outstanding performance

Strong yet lightweight, Angus Target Covered Hose has superior heat and wear characteristics due to its all-in-one construction. Resistant to abrasion, chemicals, oil, weathering, ultraviolet and ozone.

## Value for money

Exceptional robustness and storage properties ensure Angus Target Fire Hose remains in operational service years after imitation products have proven to be false economies.

## Low maintenance

Covered hose construction means that Angus Target can be wiped down after use and returned to storage without the need for drying. These excellent features ensure Angus Target outperforms all types of conventional hose.

## Angus Fire quality and experience

Angus Fire's reputation for quality and performance is built into every length of Angus Target Hose. Manufactured under BS EN ISO 9001: 2008 Quality Management Systems, all stages of production and testing are controlled by Angus Fire.

## Construction

Angus Target Fire Hose features a circular woven all-synthetic high performance textile reinforcement, totally encapsulated in a specially formulated high grade synthetic rubber.

Each length is manufactured under the controls of our BS EN ISO 9001: 2008 Quality Management System and to comply with the requirements of BS 6391: 2009. All raw materials are fully tested and inspected to ensure product quality, reliability and consistent performance.

## Applications

- Building protection
- General industry
- Municipal fire services
- Petrochemical plants
- Airports
- Military
- Power plants
- Harbours and jetties
- Shipping

### Nominal Technical Specification

	1½ / 38	1¾ / 45	2 / 52	2½ / 65	2¾ / 70
Diameter – inch/mm	1½ / 38	1¾ / 45	2 / 52	2½ / 65	2¾ / 70
Standard colour	Red	Red	Red	Red	Red
Weight (excluding couplings) kg/30m	9.0	11.0	12.8	17.0	18.3
Average short length burst pressure (bar)	52	52	52	52	52
Nominal 3:1 safety ratio – maximum advised working pressure (bar)*	17	17	17	17	17
Temperature range °C	-20 to +50				

\* or maximum working pressure of attached couplings, whichever is the lower

## INTERNATIONAL SALES

**Angus Fire Ltd**  
Angus House, Haddenham Business Park,  
Pegasus Way, Haddenham, Aylesbury, HP17 8LB, UK  
Tel: +44 (0)1844 293600 • Fax: +44 (0)1844 293664

## UK SALES

**Angus Fire Ltd**  
Station Road, Bentham, Lancaster, LA2 7NA, UK  
Tel: +44 (0)1524 264000 • Fax: +44 (0)1524 264180

Angus Fire operates a continuous programme of product development. The right is therefore reserved to modify any specification without prior notice and Angus Fire should be contacted to ensure that the current issues of all technical data sheets are used.

© Angus Fire  
6727/2 03.14