

747 Self Contained Siren



- 105dB output at 12VDC
- 2 tones – steady and warble
- Durable ABS plastic
- 15 watt power rating
- Attractive designer case
- Easy mounting
- Hardware included
- High quality mylar cone
- Heavy duty magnet

Specifications:

- Voice coil impedance – 8 ohm
- Voice coil diameter – 20mm
- Cone diameter – 87mm

Speaker Type: Mylar cone

Input Voltage: 6 – 15VDC

dB Output: 105dB at 12VDC at 3m

Current Draw: 400mA at 12VDC 8 ohm load

Operating Temp: 0°C to 50°C

Tone Frequency:

- Steady – 1200HZ
- Warble – 800HZ to 1200 HZ
- 1 Second ramp cycle

Magnet Weight: 71g

Dimensions: 102mm x 102mm x 51mm

702 Electronic Siren (Self Contained)



- 6 to 12 volt DC combination speaker and siren driver
- Extremely loud siren
- Dual channel (yelp or steady)
- Weather resistant housing with horn throat gas kit
- Enclosed wires, easily tamper protected
- 30 Watt power rating
- 118 db at 3m (12 volts)
- Protective cabinet available
- Built-in Tamper Plate protects wires from attack

How to Order:

Electronic siren – 6 to 12 volts DC

702: 2 sounds

743BE: Cabinet only

955WH: Tamper switch

28-2: Bracket for tamper