

AACU-EOL

Alarmline II Analogue LHD Part – EOL module

General

The AACU-EOL is a replacement End-Of-Line unit for use with the Alarmline II Analogue Liner Heat Detection (LHD) cable control unit. The AACULP and AACUSP control units are supplied with an AACU-EOL included, but in case the unit is lost or damaged then the AACU-EOL can be supplied separately.



Details

- UL521 and CE approval, UL/ULC listed

AACU-EOL

Alarmline II Analogue LHD Part – EOL module

Technical specifications

Physical

Physical dimensions	60 x 75 x 30mm
---------------------	----------------

Environmental

Operating temperature	0 to +125°C
-----------------------	-------------

Environment	Indoor, Outdoor
-------------	-----------------

IP rating	IP65
-----------	------

Operating temperature (max)	0 to +125°C
-----------------------------	-------------

Relative humidity	0% to 95%
-------------------	-----------

Regulatory

Certification	CE, UL
---------------	--------

Operating voltage

20 – 28VDC

Current consumption

<100mA

Mechanical

Dimensions (W x H x D)	60 x 75 x 30mm
------------------------	----------------



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit firesecurityproducts.com online or contact your sales representative.

Last updated on 24 August 2022 - 10:22