

Indoor Speed Dome Camera



Features



- 35x or 22x optical zoom, 16x digital zoom
- Day & Night (option: IR-Cut filter Removable, ICR)
- On Screen Display (OSD) set-up menu
- 128 present points
- Remote Control via RS-485 (by RYK-8330 control keyboard)
- In-Ceiling or Surface installation application



• Surface



• In-ceiling



Embedded Mount

Controller :



RYK-8330
(RS-485)

| Model No. | RYK-2E00 | RYK-2E01 | RYK-2E02 | RYK-2E03 |
|---------------------|---|--|--|--|
| Image Device | 1/4" Color Sony Super HAD (Hi-Res.) | 1/4" Color Sony Super HAD | 1/4" Color Sony EX-View HAD (Hi-Res.) | |
| Picture Elements | NTSC:768x494, PAL:752x582 | NTSC:510x492, PAL:500x582 | NTSC:768x494, PAL:752x582 | |
| Resolution | 470 TVL | 330 TVL | 470 TVL | |
| Min. Illumination | 0.7 Lux / F1.6 | 0.1 Lux (Night / BW), 0.3 Lux (Day / Color) / F1.6~3.7 | 0.01 Lux (Night / BW), 0.5 Lux (Day / Color) / F1.6~3.7 | |
| Electronic Shutter | NTSC:1/60~1/30,000, PAL:1/50~1/30,000 | | | |
| Lens Furnished | 22x Auto Focus Zoom (3.9~85.8mm / F1.6~3.7) | 22x (ICR) Auto Focus Zoom (3.9~85.8mm / F1.6~3.7) | 35x (ICR) Auto Focus Zoom (3.6~126mm / F1.6~4.2) | |
| Digital Zoom Ratio | Basic 16x (Total Zoom Ratio 352x), 2x~16x variable | | | Basic 16x (Total Zoom Ratio 560x), 2x~16x variable |
| Zoom Speed | 5 sec | | | 8 sec |
| Focus Mode | Auto / Manual / Push Auto | | | |
| Iris Control | Auto / Manual | | | |
| White Balance | Auto / Hue / Indoor / Outdoor / manual / Push Auto | | | |
| Day / Night (ICR) | — | AE / Sensor / Day / Night | | |
| Gain Control | Auto / Manual | | | |
| Back Light Comp. | On / Off | | | |
| Pan / Tilt | Angle | Pan: 360°, Tilt: 0°~90° | | |
| Control | Speed Control | Manual: Pan 1°~150° / sec, Tilt: 1°~100° / sec, Auto: Pan 1°~300° / sec, Tilt: 1°~200° / sec | | |
| Preset Point | 128 preset points | | | |
| Sequence | 6 | | | |
| Remote Control | RS-485 | | | |
| Compatible Protocol | YOKO / PELCO D&P / LG | | | |
| On Screen Display | Set-up menu | | | |
| Auto Turn Around | Yes | | | |
| Alarm / Relay | 6 / 1 | | | |
| Sync. System | Internal | | | |
| Video Output | 1 Vp-p / 75 Ohms | | | |
| Power Supply | DC12V±10% | | | |
| Power Consumption | 1083mA max. | | | |
| Operating Temp. | -10°C ~ 50°C | | | |