

RYK-2G93L/2, 2G97L/2



20M Dome Camera

FEATURES

- 600~700 TV Line
- Support AWB, AGC, AES and DNR[RJK-2G97/2]
- 3-AXIS Mechanism for Free Lens Rotation
- Optional: VF:Vari-Focal DC Lens 2.8~10.5mm (without ICR)
VR:Vari-Focal DC Lens 2.8~10.5mm (with ICR)
VT:Vari-Focal Fixed Lens 3~9mm
24 Pieces IR-LED (up to 20M)
External OSD Interface



DIMENSIONS



SPECIFICATIONS

Model No.	RYK-2G93L/2	RYK-2G97L/2
Image Device	1/3" Color Hi-Res. CCD	1/3" Color Sony Exview HAD II CCD
Picture Elements	NTSC:768x494, PAL:752x582	NTSC: 976x494, PAL: 976x582
Resolution	600 TVL	700 TVL
Min. Illumination	0.1 Lux @ F1.2	0.01 Lux @F1.2
S/N Ratio	More than 50dB	
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50~1/100,000	
Gamma	0.45	
Iris Control	DC / Auto / Manual	
Lens Furnished	3.6mm / F1.2 (Option:4.3 / 6 / 12mm)	
Sync. System	Internal	
Power Supply	DC12V±10%	
Power	IR On	310mA
Consumption	IR Off	110mA
Operating Temp.	-10°C ~ 50°C	

RYK-2G49L/2, 2G79L/2



20M Dome Camera

FEATURES

- 420~540 TV Line
- Support AWB, AGC and AES
- 3-AXIS Mechanism for Free Lens Rotation
- Optional: VF:Vari-Focal DC Lens 2.8~10.5mm (without ICR)
VR:Vari-Focal DC Lens 2.8~10.5mm (with ICR)
VT:Vari-Focal Fixed Lens 3~9mm
24 Pieces IR-LED (up to 20M)



DIMENSIONS



SPECIFICATIONS

Model No.	RYK-2G49L/2	RYK-2G79L/2
Image Device	1/3" Color Sony Super HAD II CCD	1/3" Color Hi-Res. CCD
Picture Elements	NTSC:510x492, PAL:500x582	NTSC:768x494, PAL:752x582
Resolution	420 TVL	540 TVL
Min. Illumination	0.05 Lux @ F1.2	0.1 Lux @ F1.2
S/N Ratio	More than 48dB	
Electronic Shutter	NTSC: 1/60~1/100,000, PAL: 1/50~1/100,000	
Gamma	0.45	
Iris Control	DC / Auto / Manual	
Lens Furnished	3.6mm / F1.2 (Option:4.3 / 6 / 12mm)	
Sync. System	Internal	
Power Supply	DC12V±10%	
Power	IR On	290mA
Consumption	IR Off	90mA
Operating Temp.	-10°C ~ 50°C	