

RYK-H222/1



HD CCTV Indoor Dome Camera (Board Lens)

FEATURES

- 1/2.8 3.0 Megapixel Progressive Scan CMOS
- Sony "Exmor" Technology Support Min. Illumination
- 1080P Full HD Resolution Support
- Real Time Video up to 30FPS
- HD-SDI Output
- 2D Noise Reduction
- Built-in Megapixel Board Lens
- Built-in 24 Pieces IR-LED (up to 20M) [RYK-H222L2/1]
- 3-AXIS Mechanism Design



DIMENSIONS



SPECIFICATIONS

Model No.	RYK-H222/1	RYK-H222L2/1	
VIDEO	Image Device	1/2.8" Color Sony Exmor 3.0 Megapixel CMOS	
	Picture Elements	Approx. 3M (1920H x 1080V)	
	Resolution (Frame Rates)	1080_25P / 1080_30P	
	Illumination	0.1 Lux @ F1.2 Color Mode	
	S/N Ratio	More than 50dB	
	Electronic Shutter	Auto: 1/50(60)~1/100,000	
LENS	Gamma	0.45	
	Lens Drive Type	Board Lens 4mm / F2.0	
	Aspect Ratio	16:9	
	Iris Control	Fixed	
DAY / NIGHT	IR-Cut filter Removable	N/A	Yes
	Day & Night	Day	External
	Infrared Luminary	N/A	24 Pieces IR- LED
	Illumination Distance	N/A	20 M
	Wavelength	N/A	850 nm
	Light Transistor	N/A	Yes
FUNCTIONS	On-Screen-Display (OSD)	N/A	
	Language	N/A	
	Digital Noise Reduction (DNR)	On	
	White Balance	Auto	
	Gain Control	Auto	
GENERAL	Video Output	HD-SDI (BNC)	
	Dimension (incl. BNC)	128x98mm	
	Power Supply	DC12V	
	Power Consumption	650mA	
	Operating Temp.	-10°C ~ 50°C (14°F to 122°F)	